




passive fire protection and insulation

Suppliers of passive fire products,
acoustic and specialist insulation
Manufacturers of the Safire® Fire Stopping Range

Uniclass	EPIC
CI/SIB	

Safire® Intumescent Door Seals

30/60
mins mins



- Intumescent material is high pressure & multi-directional
- High performance seals reduce smoke, acoustic and air infiltration
- Rigid outer casing for added durability
- Self-adhesive backing for easy application

The Safire® range of Intumescent Door Seals provide the traditional seal for fire rated timber door edges and frames. They are suitable for rebates in timber door leafs or frames in single or double action, single and double doors. The seals are suitable for new build and retro-fit applications.

Safire® Door Seals are supplied in 2.1m lengths and are quick and easy to fit with no special tools required. They are supplied with an acrylic self-adhesive tape backing to make application fast and easy.

Safire® Door Seals are tested to BS476 Part 22 - 1987 and other international standards, and are compliant with the requirements given in Certifire TS35.



SAFIRE a brand of Fireus Ltd.

Fireus Ltd.

Unit 6 Thetis Road, Lune Industrial Estate, Lancaster, LA1 5QP

Tel. 01524 388898 | Fax. 01524 383724 | Email. info@fireus.co.uk | Web. www.fireus.co.uk

Installation Instructions

1. Select the appropriate seal using the door test evidence which will identify the size of intumescent seal required.

2. If the sealing system is not identified, Fireus recommend the installation of 15mm x 4mm for 30 minute or a 20mm x 4mm for 60 minutes.

3. The seal needs to be located centrally in either the door leaf or frame.

4. Route a groove suitable for the size of intumescent seal selected. Clean the rebate to remove any dust. Remove the release liner from the product and push fit into the routed groove.

5. To achieve best adhesion the seals must be applied to clean dry surfaces at temperatures between +5°C and +40°C.


Storage

Store in a cool dry place not above 35°C and ensure sufficient ventilation.

Available Sizes

Size	FO	PO	P+F	SF	TF	SDF	DF	Fire Res.
10 x 4	8500	8512	8510	8524	8523	8923	30102	30 mins
15 x 4	8700	8712	8710	8724	8723	8924	30103	30 mins
20 x 4	8600	8612	8610	8624	8623	8925	30104	60 mins
25 x 4	8800	8812	8810					60 mins
30 x 4	30094	3009412	3009410					60 mins
38 x 4	30076	3007612	3007610					60> mins

FO - Fire Only, PO - Pile Only, P+F - Pile with Fin, SF - Single Flipper, TF - Twin Flipper, SDF - Side Flipper, DF - Double Flipper




10 x 4 Fire Only Door Seal

Dimensions: 10mm x 4mm
Lengths: 1050mm, 2.1 metres.
Finishes: Brown or White
Tube Qty: 125.



20 x 4 Fire Only Door Seal

Dimensions: 20mm x 4mm
Lengths: 1050mm, 2.1 metres.
Finishes: Brown or White
Tube Qty: 50.



10 x 4 Fire & Smoke Seal

Dimensions: 10mm x 4mm
Lengths: 1050mm, 2.1 metres.
Finishes: Brown or White
Tube Qty: 75.



20 x 4 Fire & Smoke Seal

Dimensions: 20mm x 4mm
Lengths: 1050mm, 2.1 metres.
Finishes: -Brown or White
Tube Qty: 35.

Other products in the Fireus Products range:

FIRE BARRIERS: Total Comfort Rock Fibre Fire Blanket

FIRE STOPPING: Compound
Fire Collars
Barriers (Batts)
Sealants
Fire Pillows
Expansion Joints
Flamestop60
Flamestop FSI

THERMAL: Industrial thermal and acoustic insulation

For information on any of the above, or the name of your nearest distributor, please contact our sales department on tel. 01524 388898.

Alternatively, product information is available from our web site at www.fireus.co.uk

Your distributor:



Fireus Ltd.

Unit 6 Thetis Road, Lune Industrial Estate, Lancaster, LA1 5QP

Tel. 01524 388898 | Fax. 01524 383724 | Email. info@fireus.co.uk | Web. www.fireus.co.uk